

Acrylic Emulsion Polymerization Technology

技术持有人: 魏克海先生

Technology Holder: Mr. Wei Kehai

地址: 山东省淄博市张店区新村路东首

ADD: Xincun Road,Zhangdian,Zibo,Shandong,PRC

TEL: 8613953363746

FAX: 0533-2802284

P.C.: 255000

WEBPAGE: <http://www.acrylic-poly.com/> <http://www.ruyejishu.cn/>

E-MAIL: houshuwei01@126.com 13953363746@139.com

EC-510 Glass Sealant Emulsion

■ Summary

EC-510 Glass Sealant Emulsion is an anionic emulsion polymerized from acrylic and its lipid monomer, styrene and functional monomer.

■ Physical and Chemical Indicators

Product	Project	Result
EC-510 Emulsion	Appearance	Milky white light blue viscous liquid
	PH	4.5~6.5
	Viscosity	100~250 CPS
	Solid content	(50±1)%
	Water resistance	Excellent
	Bonding fastness	Excellent
	Shelf life	6 months(5℃~25℃ storage)

■ Performance and Application

EC-510 Glass Sealant Emulsion has excellent adhesive strength and excellent flexibility. It can be made into transparent glass glue with alkaline substance and auxiliary agent. It is used for bonding and sealing glass door, glass decorations, fish tank, glass curtain wall and so on.