

Acrylic Emulsion Polymerization Technology

技术持有人: 魏克海先生

Technology Holder: Mr. Wei Kehai

地址: 山东省淄博市张店区新村路东首

ADD: Xincun Road,Zhangdian,Zibo,Shandong,PRC

TEL: 8613953363746

FAX: 0533-2802284

P.C.: 255000

WEBPAGE: <http://www.acrylic-poly.com/> <http://www.ruyejishu.cn/>

E-MAIL: houshuwei01@126.com 13953363746@139.com

AT-623 Thickener

■ Summary

AT-623 Thickener is a kind of alkali swelling emulsion thickener, which is composed of acrylic ester and functional monomer and cross-linked monomer.

■ Physical and Chemical Indicators

Product	Project	Result
AT-623 Thickener	Appearance	Milky white light blue liquid
	PH	7.5~11.0
	Viscosity	<50 CPS
	Solid content	(30±2)%
	Shelf life	6 months(5℃~25℃ storage)

■ Performance and Application

AT-623 thickener is a kind of low viscosity polymer emulsion. It is widely used in water paint, ink thickening, small amount, no extinction, stable storage, not easy to mildew. The water paint, thick coating ink without falling, the good feeling in the construction, no brush, no nozzle, are the best additives in the building coating, fabric coating, electrostatic flocking and adhesive production.