

Acrylic Emulsion Polymerization Technology

技术持有人: 魏克海先生

Technology Holder: Mr. Wei Kehai

地址: 山东省淄博市张店区新村路东首

ADD: Xincun Road,Zhangdian,Zibo,Shandong,PRC

TEL: 8613953363746

FAX: 0533-2802284

P.C.: 255000

WEBPAGE: <http://www.acrylic-poly.com/> <http://www.ruyejishu.cn/>

E-MAIL: houshuwei01@126.com 13953363746@139.com

Introduction of new R & D products

Tert Butyl Acrylate Self-crosslinkable Acrylic Emulsion

■ Performance

The physical and chemical indexes of the product all reach or exceed the performance indexes of styrene acrylic and acrylic emulsion, and the indexes of film forming, leveling and environmental protection have been greatly improved.

■ Cost

The cost is about 80% of the styrene acrylic emulsion, which is about 70% of the pure acrylic emulsion.

■ Main Varieties and Their Uses

- Interior wall paint emulsion (used for interior wall latex paint, no benzene, more environmentally friendly, leveling good);
- (used for exterior wall emulsion paint, lacquer, finish);
- JS waterproof emulsion (used for toilet, bathroom, pond and roof, roof waterproof coating);
- Glass fiber mesh fabric setting emulsion (used for grid exterior wall insulation strengthening network);
- Wood paint emulsion (used to produce a variety of children's toys, living furniture, office furniture, decorative board and other water-based paint);
- Glass paint emulsion (for the production of cosmetics bottles, bottles, glass walls and other decorative paint);
- Metal paint emulsion (for the production of various metal surface with paint, such as antirust paint, topcoat, color plate paint, is likely to do car paint, etc.);
- Emulsion of textiles (for textile colouring, sizing, printing, and screen printing adhesives)